

1.00in [25mm]
(MAX INTONATION
TO CENTER OF
PIVOT HOLE)

STUD
3/16in HEX
ADJUST


0.750in [19.1mm]

1.000in [25.4mm]

0.18in [5mm]
(MIN INTONATION
TO CENTER OF
PIVOT HOLE)

0.375in [9.5mm]
BRIDGE PLATE

Scale



1.500in [38.1mm]

WEIGHT (WITH MOUNTING HARDWARE): 19.0oz [539g]

0.43in [11mm]
(MIN STRING HEIGHT)

0.708in [18.0mm]
(STRING SPACING)

USE 1MM HEX
WRENCH

0.486in [12.3mm]

3.406in [86.5mm]
(PIVOT POST)

4.185in [106.3mm]

2.000in [50.8mm]

0.220in [5.6mm]

0.220in [5.6mm]

1.014in [25.8mm]

USE 1/2 in [12.7mm] BORE

INSERT

0.750in [19.1mm]

THIS DRAWING IS THE SOLE PROPERTY OF HIPSHOT PRODUCTS, INC. ALL RIGHTS ARE RESERVED. DIMENSIONS AND PRODUCT FEATURES MAY CHANGE WITHOUT NOTICE.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCE: ± .005

REV DATE: 2/1/2022

5V400-708 4 STG BASS
VIBRATO BRIDGE 708
SPACING DIMENSIONS



8248 STATE ROUTE 96
Interlaken, NY 14847 U.S.A.
TEL: 607-532-9404 FAX: 607-532-9530
E-MAIL: info@HipshotProducts.com